

Page 1 of 9

CND-N-137

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards MSDS Revision: 1.4 MSDS Revision Date: 08/03/2009 1. PRODUCT IDENTIFICATION 1.1 Product Name: FREE: COLOUR / EFFECTS 1.2 SOLVENT POLYMER BLEND/NAIL LACQUER, NITROCELLULOSE LACQUER 1.3 Synonyms: NA 1.4 Trade Names: CND ENAMEL Product Use: 1.5 COSMETIC USE ONLY Distributor's Name 1.6 CREATIVE NAIL DESIGN, INC. 1.7 Distributor's Address 1125 JOSHUA WAY, VISTA, CA USA 92081 **Emergency Phone** CHEMTREC: +1 (800) 424-9300 / +1 (703) 527-3887 (800) 833-NAIL (6245), (760) 599-2900 2. HAZARD IDENTIFICATION 2.1 Hazard Identification: This product is classified as a HAZARDOUS SUBSTANCE and as DANGEROUS GOODS according to the classification criteria of NOHSC:1088 (2004) and ADG Code (Australia). Flammable liquid. 2.2 Routes of Entry: Inhalation: YES Absorption: YES YES Ingestion: Effects of Exposure INGESTION: If product is swallowed, may cause nausea, vomiting and/or diarrhea and central nervous system depression. EYES: Mildly to moderately irritating to the eyes. Symptoms of overexposure may include redness, itching, irritation and watering. SKIN: May be irritating to skin in some sensitive individuals, especially after prolonged contact. INHALATION: Vapors of this product may be slightly irritating to the nose, throat and other tissues of the respiratory system. Symptoms of overexposure can include coughing, wheezing, nasal congestion, and difficulty breathing. Inhalation of vapors exceeding the levels listed in Section 3 (Composition & Ingredient Information) can cause central nervous system depression (e.g., drowsiness, dizziness, headaches, nausea). Symptoms of Overexposure: EYES: Overexposure in eyes may cause redness, itching and watering. SKIN: Symptoms of skin overexposure in some sensitive individuals may include redness, itching, and irritation of affected areas. 2.5 Acute Health Effects FYFS: Mild to moderate irritation to eves near affected areas. SKIN: Mild to moderate irritation to skin near affected areas. INHALATION: High concentrations of vapors can cause drowsiness, dizziness, headaches and nausea. 2.6 Chronic Health Effects: None known. 2.7 Target Organs Eyes, skin & respiratory system. NA = Not Available; ND = Not Determined; NE = Not Established; NF = Not Found; C = Ceiling Limit; See Section 16 for Additional Definitions of Terms Used. Note: All WHMIS required information is included. It is located in appropriate sections based on the ANSI Z400.1-2004 format.



*Not a hazard with this product.

MATERIAL SAFETY DATA SHEET

Page 2 of 9

CND-N-137

Prepared to OSHA, ACC, ANSI, NO	OHSC, WHMIS &	& 2001/58 EC :	Standards	MSDS R	evision	: 1.4		MSDS	Revisio	n Date	e: 08/0	3/2009)
	3. COM	<u>APOSITION</u>	N & INGR	EDIEN	T INF	ORN							
					400	- III			IMITS I			1 ³)	
					ACC pp		r	NOHSC ppm	•		OSHA ppm		OTHER
					рр	111	ES-	ES-	ES-		ррпп		OTTLER
CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	TLV	STEL	TWA	STEL	PEAK	PEL	STEL	IDLH	
BUTYL ACETATE	123-86-4	AF7350000	204-658-1	< 45.0	150	200	150	200	NF	150	200	1700	150 TWA
ETHYL ACETATE	141-78-6	AH5425000	201-550-6	< 30.0	200	400	200	400	NF	NA	NA	2000	400 TWA
NITROCELLULOSE	9004-70-0	QW0970000	NA	< 15.0	(10)	NE	NF	NF	NF	(10)	NE	NE	
ACETYL TRIBUTYL CITRATE	77-90-7	TZ8330000	201-067-0	< 10.0	NA	NA	NF	NF	NF	NA	NA	NA	
PHTHALIC ANHYDRIDE/TRIMELLITIC ANHYDRIDE/GLYCOLS COPOLYMER	NA	NA	NA	< 10.0	NA	NA	NF	NF	NF	NA	NA	NA	
ISOPROPYL ALCOHOL	67-63-0	NT8050000	200-661-7	< 10.0	400	500	400	500	NF	400	500	2000	400 TWA
ADIPIC ACID/FUMARIC ACID/PHTHALIC ACID/TRICYCLODECANE DIMETHANOL COPOLYMER	NA	NA	NA	< 5.00	NA	NA	NF	NF	NF	NA	NA	NA	
STEARALKONIUM HECTORITE	94891-33-5	NA	NA	< 5.00	NE	NE	NF	NF	NF	NE	NE	NE	
CITRIC ACID	77-92-9	GE7350000	201-069-1	< 0.10	NA	NA	NF	NF	NF	NA	NA	NA	
MICA	MAY ALSO 12001-26-2	O CONTA	IN THE FC	>LLOW < 10.0		CHE	(2.5)	ALS:	NF	30	NA NA	NA NA	RESP
MICA	12001 20 2			-	110		-			30	ויי	110	FRAC*
TITANIUM DIOXIDE	13463-67-7	XR2275000	236-675-5	< 6.0	10	NA	NF	NF	NF	10	NA	NA	
ADIPIC ACID/NEOPENTYL GLYCOL/TRIMELLITIC ANHYDRIDE COPOLYMER	28407-73-0	NA	123-86-4	< 2.0	NA	NA	NF	NF	NF	NA	NA	NA	
ETHYL TOSYLAMIDE	1077-56-1	NA	214-073-3	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
SYNTHETIC FLUORPHLOGOPITE	12003-38-2	NA	234-426-5	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
CALCIUM ALUMINUM BOROSILICATE	6599-17-3	LK3651000	266-046-0	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
CALCIUM SODIUM BOROSILICATE	6599-17-3	NA	266-046-0	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
SUCROSE ACETATE ISOBUTYRATE	126-13-6	WN6550000	204-771-6	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
DIMETHICONE	9006-65-9	NA	NA	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
TIN OXIDE	18282-10-5	XQ4000000	242-159-0	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
DIISOBUTYL ADIPATE	141-04-8	AV1480000	205-450-3	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
SILICA	1317-95-9	VV7336000	239-487-1	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
					1	1							1



Page 3 of 9

CND-N-137

Prep	ared to OSHA,	ACC, ANSI, NO	HSC, WHMIS 8	& 2001/58 EC S	tandards I	MSDS Re	evision:	1.4		MSDS	Revisic	n Date	e: 08/0	3/2009)
		2 0	CAADOCIT		PDEDIENT	INIEO	DAAA	TION		ntin					
AA A V :	CONTAIN THESE		.OMPOSII	ION & INC	JKEUIENI	INFO	κMΑ		N- CC	ntin	vea		1		
	499 (IRON OXII		1317-61-9	NA	NA	< 5.0	NA	NA	NF	NF	NF	NA	NA	NA	
	891 (TITANIUM I		13463-67-7	XR2275000	236-675-5	< 5.0	10	NA	NF	NF	NF	10	NA	NA	
	163 (BISMUTH C			NA	232-122-7	< 2.0	NA	NA	NF	NF	NF	NA	NA	NA	
)90 (BLUE 1LAKE		3844-45-9	BQ4725000	223-339-8	< 2.0	NA	NA	NF	NF	NF	NA	NA	NA	
	140 (YELLOW 5 I		1934-21-0	UQ6400000	217-699-5	< 2.0	NA	NA	NF	NF	NF	NA	NA	NA	
CI 158	350 (RED 6 LAKE	<u> </u>	5281-04-9	QJ1975000	226-109-5	< 2.0	NA	NA	NF	NF	NF	NA	NA	NA	
CI 15	850 (RED 7 LAK	E)	5858-81-8	QJ1975000	227-497-9	< 2.0	NA	NA	NF	NF	NF	NA	NA	NA	
CI 158	380 (RED 34 LAK	(E)	64-17-83-0	NA	229-142-3	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
CI 770	000 (ALUMINUM	POWDER)	7429-90-5	BD0330000	231-072-3	< 1.0	NA	NA	10	NF	NF	NA	NA	NA	DUST*
CI 774	191 (IRON OXID	ES)	1332-37-2	NO7400000	215-570-8	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
	510 (FERRIC AM OCYANIDE)	MONIUM	14038-43-5	LJ8200000	237-875-5	< 1.0	NA	NA	NF	NF	NF	NA	NA	NA	
*Not	a hazard with t	his product.													
				A EIF	RST AID M	EACII	DEC								
4.1	First Aid:			4. FII	(3) AID M	EAJU	KES								
	INGESTION:	emergency to	elephone nur	G. Contact C nber for assist 1's head lower	ance and ins	truction	s. See	k imm	ediate	medi					
	EYES:	•	•	vever, if produ eyelid(s) to ens	•									for at	least 15
	SKIN:	affected area	a with soap a	uct is on the sl and water. Do g persists, cont	not wear co	ontamin	ated c	lothing							
	INHALATION:	Remove victi	m to fresh air	rat once. Un			-		ing sto	ps, pe	erform	artifici	al resp	oiration	n. Seek
4.2	Medical Condition	s Aggravated by Ex	kposure:												
				5 EIDEI	IGHTING	MEA	CIIDE	•							
5.1	Flashpoint & Metho	od: CC Estimated I	based on Fthy		ISIIIING	IVILA.	JUNE	<u>J</u>							
5.2	Autoignition Temp		and a on Emy												
5.3	Flammability Limits	:		Lower Explosiv	e Limit (LEL):		NE	U	pper E	xplosiv	e Limit	(UEL):		NE	
5.4	Fire & Explosion Ha WARNING: Ex container clos	xtremely Flam	mable! Keep	away from h	eat, lit cigare	ttes, sp	arks &	open	flame.	Keep	•			_	
5.5		ry Chemical, Fo	oam or Water,	, as authorized									1		
5.6	First responde	lures: d in a fire, this p rs should wear lse a water spro	eye protecti	on. Structural	firefighters m	ust wea	r SCBA	s and	full pro	tective					7
		a fire involving		tauce or allec	i vapois. War	ei illuy	noi be	enecti	ive in C	icioali					



Body Protection:

water.

No apron required when handling small quantities.

MATERIAL SAFETY DATA SHEET

Page 4 of 9

CND-N-137

1

3

0

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards MSDS Revision Date: 08/03/2009 MSDS Revision: 1.4 6. ACCIDENTAL RELEASE MEASURES 6.1 Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment. For small spills (e.g., < 1 gallon (3.785 liters)) wear appropriate personal protective equipment (e.g., goggles, gloves). Maximize ventilation (open doors and windows) and secure all sources of ignition. Remove spilled material with absorbent material and place into appropriate closed container(s) for disposal. Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with plenty of warm water and soap. Remove any contaminated clothing and wash thoroughly For spills ≥ 1 gallon (3.785 liters), deny entry to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Use ONLY non-sparking tools for recovery and cleanup. Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for proper disposal. Remove contaminated clothing promptly and wash affected skin areas with soap and water. Keep spills and cleaning runoffs out of municipal sewers and open bodies of water. 7. HANDLING & STORAGE INFORMATION 7.1 Work & Hygiene Practices: Avoid prolonged or repeated contact with skin. Avoid breathing vapors of this product. Use in a well-ventilated location (e.g., local exhaust ventilation, fans). Do not eat, drink or smoke while handling product. 7.2 Keep this material away from heat, sparks and open flame. Open containers slowly on a stable surface. Keep container closed tightly when not in use. Empty container may contain residual amounts of this product; therefore, empty containers should be handled with Store containers in a cool, dry location, away from direct sunlight, other light sources, or sources of intense heat. Store away from incompatible materials (see Section 10). 7.3 Open containers slowly on a stable surface. Keep container tightly closed when not in use. Empty containers may contain residual amounts of this product; therefore, empty containers should be handled with care. 8. EXPOSURE CONTROLS & PERSONAL PROTECTION 8.1 Ventilation & Engineering Controls: When working with large quantities of product, provide adequate ventilation (e.g., local exhaust ventilation, fans). Ensure that an eyewash station, sink or washbasin is available in case of exposure to eyes. 8 2 Respiratory Protection: No special respiratory protection is required under normal conditions of use or handling. If necessary, use only respiratory protection authorized per U.S. OSHA's requirement in 29 CFR §1910.134, or applicable U.S. state regulations, or the appropriate standards of Canada, its provinces, E.C. member states, or Australia. 8.3 Eve Protection:

None required under normal conditions of use. Avoid eye contact. May cause irritation in some sensitive individuals. When handling

HEALTH

FLAMMABILITY

PROTECTIVE EQUIPMENT

REACTIVITY

large quantities (e.g., ≥ 1 gallon (3.785 liters)), safety glasses with side shields should be used.

When handling large quantities (e.g., \geq 1 gallon (3.785 liters)), eye wash stations and deluge showers should be available. Upon completion of work activities involving

large quantities of this product, wash any exposed areas thoroughly with soap and

None required under normal conditions of use. May cause skin irritation in some sensitive individuals. When handling large quantities (e.g., ≥ 1 gallon (3.785 liters)), wear nitrile, rubber or other impervious gloves.



Page 5 of 9

CND-N-137

on Date: 08/03/2009	MSDS Revision Date: 08	MSDS Revision: 1.4	001/58 EC Standards	ACC, ANSI, NOHSC, WHMIS & 20	pared to OSHA, ACC, AN	Prep
		AICAL PROPERTIES	VSICAL O CHEA	0 ви		
		IICAL PROPERTIES			Density:	0.1
				0.92-0.98 (H ₂ 0	,	
		lated	(77.2 – 108.9 °C) calcı	171 – 228 °F (Boiling Point:	9.2
				NA NA	Melting Point:	9.3
		ed	Acetate = 1) calcula	>1.0 (n-Butyl	Evaporation Rate:	9.4
			air	Heavier than	Vapor Pressure:	9.5
				NA	Molecular Weight:	9.6
		ster odor.	ous liquid with sweet e	lor: Colored visco	Appearance & Color:	9.7
				ND	Odor Threshold:	9.8
				Moderate	Solubility:	9.9
				NA	рН	9.10
			s	525 – 625 cps	Viscosity:	9.11
				VOC 2.31 lb/	Other Information:	9.12
		DE A OTIVITY	10 CTABILITY 0			
		KEACIIVIIY	10. STABILITY &		Stability:	10.1
		7 Storage and Handling)	properly (see Section	ambient conditions when stored		10.1
		7, storage and manaling)	properly (see seemon		Hazardous Decomposition Pro	10.2
apors and carbon oxid	clude irritating vapors and	al decomposition may in	the products of thern	extremely high temperatures,		
				rization:	Hazardous Polymerization:	10.3
					Will not occur. Conditions to Avoid:	0.4
	ala	os or incompatible mate	turas strang light sour	contact with extreme temperal		10.4
	uis.	es of incompande male	iores, sirong light soor		Incompatible Substances:	10.5
oric or muriatic acids), o	(e.g., hydrochloric or mu	superoxides), strong acid		incompatible with strong oxidi e.g., lye, potassium hydroxide).	This product is incomp	
		L INFORMATION	OXICOLOGICA	11. T		
					Toxicity Data:	11.1
r the components of th				nas not been tested on anima h are found in the scientific litero		
				2 2 2 2 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3	Acute Toxicity:	11.2
				3	See section 2.3	
					Chronic Toxicity:	11.3
				6	See section 2.6	
					Suspected Carcinogen:	11.4
a human carcinogen) b	t classifiable as a human o	a Group 3 carcinogen (n	, which is classified as	uct contains Isopropyl Alcohol,	Yes. This product con the IARC.	
					Reproductive Toxicity:	11.5
		S.	ctive toxicity in humar	not reported to cause reproduc	This product is not repo	
					Mutagenicity:	
		3.	genic effects in humar	not reported to produce mutag		
					Embryotoxicity:	
		ins.	otoxic ettects in humo	not reported to produce embry		
			enic effects in humans.	not reported to cause teratoge	Teratogenicity: This product is not repo	
					Reproductive Toxicity:	
					Reproductive Toxicity:	



Page 6 of 9

CND-N-137

MSDS Revision: 1.4 MSDS Revision Date: 08/03/2009 Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards 11. TOXICOLOGICAL INFORMATION-continued 11.6 Irritancy of Product: See section 2.3 11.7 Biological Exposure Indices: Physician Recommendations: Treat symptomatically. 12. ECOLOGICAL INFORMATION Environmental Stability: The components of this product will slowly degrade over time into a variety of organic compounds. Specific environmental data available for the components of this product are as follows: Butyl Acetate: K_{OC} = 1.82. Water solubility: 120 parts H_2O at 25 °C (77°F). Bioconcentration Factor = 4-14. Bioconcentration is not anticipated to be significant. This compound can be removed from contaminated environments from volatilization, and biodegradation. This compound's half-life in water is 6.1 hours. Ethyl Acetate: $K_{OC} = 0.73$. Water solubility: 64,000 mg/l. Bioconcentration Factor = 4-14. Bioconcentration is not anticipated to be significant. This compound can be removed from contaminated environments from volatilization, and biodegradation. This compound's half-life in water is 6.1 hours. Isopropyl Alcohol: Log Kow = 0.05-0.14. Isopropyl alcohol occurs naturally; it is generated during microbial degradation of plant and animal wastes. When released on land or water, it is apt to volatilize and biodegrade. The estimated half-life in water is 5.4 days. Isopropyl alcohol is not expected to bioconcentrate. 12.2 Effects on Plants & Animals: There are no specific data available for this product. 12.3 Effects on Aquatic Life: There are no specific data available for this product; however, very large releases of this product may be harmful or fatal to overexposed aquatic life. 13. DISPOSAL CONSIDERATIONS Waste Disposal: 13.1 Dispose of in accordance with all Federal, state, and local regulations. 13.2 Special Considerations U.S. EPA WASTE NUMBER: D001 (characteristic - ignitable)



Page 7 of 9

CND-N-137

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards

MSDS Revision: 1.4

MSDS Revision Date: 08/03/2009

14. TRANSPORTATION INFORMATION

The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG, SCT, ADGR and the CTDGR.

14.1	49 CFR (GND):
	CONSUMER COMMODITY, ORM-D (≤ 1.0 L)
	UN1263, PAINT, 3, II (> 1.0 L)
14.2	IATA (AIR):
	CONSUMER COMMODITY, 9, ID8000 (≤ 0.5 L)
	UN1263, PAINT, 3, II (> 0.5 L)
14.3	IMDG (OCN):
	UN1263, PAINT, 3, II, LTD QTY (≤ 1.0 L)
	UN1263, PAINT, 3, II (> 1.0 L)
14.4	IDGR (Canadian GND): MARK PACKAGE "LIMITED QUANTITY" or "QUANTITÉ LIMITÉE" or "LTD QTY" or "QUANT LTÉE" (≤ 1.0 L)
	UN1263, PAINT, 3, II (> 1.0 L)
14.5	ADR/RID (EU):
	UN1263, PAINT, 3, 3 °(b), ADR, LTD QTY (≤ 1.0 L)
14.6	SCT (MEXICO):
	UN1263, PINTURA (INFLAMMABLE), 3, II, CANTIDAD LIMITADA (≤ 1.0 L)
14.7	ADGR (AUS):
	UN1263, PAINT, 3, 3 °(b), LTD QTY (≤ 1.0 L), HAZCHEM CODE: 3(Y)E





15. REGULATORY INFORMATION

15.1 U.S. EPA SARA Title III Reporting Requirements:

SARA reporting code Ethanol: acute, chronic, flammable. Section 313: No chemicals are reportable under Section 313. SARA 304 (40 CFR Table 302.4) - Butyl Acetate, Ethyl Acetate

15.2 U.S. EPA SARA Title III Threshold Planning Quantity (TPQ):

There are no specific Threshold Planning Quantities for the components of this product.

15.3 U.S. U.S. U.S. TSCA Inventory Status:

The components of this product are listed on the TSCA Inventory.

15.4 U.S. CERCLA Reportable Quantity (RQ):

Butyl Acetate: 2268 kg; 5000 lbs. Ethyl Acetate: 2268 kg; 5000 lbs.

15.5 Other U.S. Federal Requirements:

This product complies with the appropriate sections of the Food and Drug Administration's 21 CFR subchapter G (Cosmetics).

15.6 Other Canadian Regulations:::

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. Class B2 Flammable Liquid.







Page 8 of 9

CND-N-137

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards

MSDS Revision: 1.4

MSDS Revision Date: 08/03/2009

15. REGULATORY INFORMATION -continued

15.7 U.S. State Regulatory Information:

Butyl Acetate, Ethyl Acetate, and Isopropyl Alcohol are covered under specific state criteria. Components of this product are not listed on the California Proposition 65 lists or they are exempt from the requirements.

15.8 European Union 67/548/EEC and Australia NOHSC:2011 (2003) Requirements:

The primary components of this product are not listed in Annex I of EU Directive 67/548/EEC.

The primary components of this product are not listed in Annex I of EU Directive 67/548/EEC.

<u>Butyl Acetate</u>: Flammable (F). R: Flammable. S: 9-16-33 - Keep container in a well-ventilated place. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges.

Ethyl Acetate: Flammable, Harmful (F, Xn). R: 11-20-36/37 — Highly flammable. Harmful by inhalation. Irritating to eyes and respiratory system. S: 2-7-16-24/25/26 — Keep out of the reach of children. Keep container tightly closed. Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Do not empty into drains. Take precautionary measures against static discharges.

<u>Isopropanol</u>: Flammable (F). R: 11-36/37 – Highly flammable. Irritating to eyes and respiratory system. S: 2-7-16-24/25/26 – Keep out of the reach of children. Keep container tightly closed. Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice

HAZCHEM CODE: 3YE Poison Schedule: ND





16. OTHER INFORMATION

16.1 Other Information:

WARNING: EXTREMELY FLAMMABLE! Avoid inhalation. Store in a cool place. Keep out of reach of children.

16.2 Terms & Definitions:

Please see last page of this MSDS.

16.3 Disclaime

This Material Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's & Creative Nail Design's knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness are not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein related only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.

16.4 Prepared for:

Creative Nail Design, Inc. A Division of Colomer U.S.A., Inc. 1125 Joshua Way Vista, CA 92081 USA (800) 833-NAIL (6245) phone (760) 599-2900 (760) 599-4005 fax http://www.cnd.com/



Hands. Feet. Beauty.

16.5 Prepared by:

ShipMate, Inc. P.O. Box 787 Sisters, OR 97759

Phone: +1 (310) 370-3600 Fax: +1 (310) 370-5700

E-mail: shipmate.com http://www.shipmate.com/





Page 9 of 9

CND-N-137

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards

MSDS Revision: 1.4

MSDS Revision Date: 08/03/2009

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a MSDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No.	Chemical Abstract Service Number

EXPOSURE LIMITS IN AIR:

ACGIH	American Conference on Governmental Industrial Hygienists
TLV	Threshold Limit Value
OSHA	U.S. Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
IDLH	Immediately Dangerous to Life and Health

FIRST AID MEASURES:

CPR	Cardiopulmonary resuscitation - method in which a person whose heart has stopped receives manual chest compressions and breathing to circulate blood and provide oxygen to the body.
-----	--

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: HMIS

HEALTH, FLAMMABILITY & REACTIVITY RATINGS:


0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard



PERSONAL PROTECTION RATINGS:

A	S			
В	8	The second		
С	8	The second	*	
D		The second	~	
D E	€			






FLAMMABILITY LIMITS IN AIR:

Autoignition Temperature	Minimum temperature required to initiate combustion in air with no other source of ignition
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source

NA Not Available NR No Results NE Not Established ND Not Determined ML Maximum Limit SCBA Self-Contained Breathing Apparatus

NATIONAL FIRE PROTECTION ASSOCIATION: NFPA HAZARD RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard
ACD	Acidic
ALK	Alkaline
COR	Corrosive
w —	Use No Water
OX	Oxidizer



TOXICOLOGICAL INFORMATION:

Lethal Dose (solids & liquids) which kills 50% of the exposed animals s Lethal concentration (gases) which kills 50% of the exposed animal Concentration expressed in parts of material per million parts TDio Lowest dose to cause a symptom TCLo Lowest concentration to cause a symptom TDio, LDio, & LDo or Lowest dose (or concentration) to cause lethal or toxic
exposed animal Concentration expressed in parts of material per million parts TDIo Lowest dose to cause a symptom TCLO Lowest concentration to cause a symptom
parts TD ₁₀ Lowest dose to cause a symptom TCLo Lowest concentration to cause a symptom
TCLo Lowest concentration to cause a symptom
TD _{Io} , LD _{Io} , & LD _o or Lowest dose (or concentration) to cause lethal or toxic
TC, TC _o , LC _{lo} , & LC _o effects
IARC International Agency for Research on Cancer
NTP National Toxicology Program
RTECS Registry of Toxic Effects of Chemical Substances
BCF Bioconcentration Factor
TL _m Median threshold limit
log Kow or log Koc Coefficient of Oil/Water Distribution

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System
DOT	U.S. Department of Transportation
TC	Transport Canada
EPA	U.S. Environmental Protection Agency
DSL	Canadian Domestic Substance List
NDSL	Canadian Non-Domestic Substance List
PSL	Canadian Priority Substances List
TSCA	U.S. Toxic Substance Control Act
EU	European Union (European Union Directive 67/548/EEC)
CPR	Canada's Controlled Product Regulations

EC INFORMATION:

		M	*			×	×
С	E	F	N	0	T+	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful

WHMIS INFORMATION:

\oslash				(T)	®		R
Α	В	С	D1	D2	D3	E	F
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive