

Page 1 of 8

Prep	ared to OSHA, A	ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards	MSDS Rev	vision: 1.5	MSDS	Revision Date: 09/17/	2009				
	1. PRODUCT IDENTIFICATION										
1.1	Product Name:										
	SHELLAC UV TOP COAT										
1.2	Chemical Name:										
	Gel Lacquer										
1.3	Synonyms:										
	Shellac UV Top Coat										
1.4											
	SHELLAC UV Top Coat										
1.5	Product Use: COSMETIC USE										
1.6	Distributor's Name:										
1.0											
1.7	Distributor's Addres	is:									
	1125 JOSHUA	WAY, VISTA, CA USA, 92081									
1.8	Emergency Phone:										
		+1 (800) 424-9300 / +1 (703) 527-3887									
1.9	Business Phone:	. (6245), (760) 599-2900									
	(800) 855-NAII	. (6245), (780) 577-2700									
		2. HAZARD IDE									
2.1	Hazard Identificatio	-	NIIFICA								
2.1	This product	is classified as a HAZARDOUS SUBSTANCE and a		US GOODS a	ccording	to the classification	criteria of				
2.2	Routes of Entry:	2004) and ADG Code (Australia). Flammable liquic Inhalation: YES		rption:	YES	Ingestion:	YES				
2.3	Effects of Exposure		AD30	iption.	163	ingestion.	TLJ				
	INGESTION:	If product is swallowed, may cause nausea, vomitin	g and/or dia	arrhea and cer	ntral nervo	us system depression					
	EYES:	Mildly to moderately irritating to the eyes. Sympwatering.	otoms of ove	erexposure m	ay include	e redness, itching, in	itation and				
	SKIN:	May be irritating to skin in some sensitive individuals	, especially	after prolonge	d and/or r	epeated contact.					
	INHALATION:	Vapors of this product may be slightly irritating to the of overexposure can include coughing, wheezing									
		exceeding the levels listed in Section 3 (Composition	sition & Ingr								
2.4	Summer of O	depression (e.g., drowsiness, dizziness, headaches,	nausea).								
2.4	Symptoms of Overe	exposure: Overexposure in eyes may cause redness, itching a	nd watering								
	SKIN:	Symptoms of skin overexposure in some sensitive	•		redness it	china and irritation	of affected				
		areas.		indy include		ennig, and initiation					
2.5	Acute Health Effect										
	EYES:	Mild to moderate irritation to eyes near affected are									
	SKIN:	Mild to moderate irritation to skin near affected area									
27	Chronic Health Effe	High concentrations of vapors can cause drowsiness	s, dizziness, l	neadaches an	d nausea.						
2.6	None known.	9CTS:									
2.7	Target Organs:										
		spiratory system.									
NA =	Not Available;	ND = Not Determined; NE = Not Established; NF = Not	ot Found; C	= Ceiling Limit;	See Sectio	on 16 for Additional D	efinitions of				
		II WHMIS required information is included. It is locate									



Page 2 of 8

Prep	Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards					MSDS Revision: 1.4 MSDS Revision Date: 09/03/2009						9			
3. COMPOSITION & INGREDIENT INFORMATION															
								<u></u>			<u>IMITS II</u>	N AIR (1
								GIH		NOHSC ppm	•		OSHA		OTHER
							pp		ES-	ES-	ES-		ppm		OTHER
	CHEMICAL NA	AME(S)	CAS No.	RTECS No.	EINECS No.	%	TLV	STEL	TWA	STEL	PEAK	PEL	STEL	IDLH	
PROP	RIETARY FORMU	LA	NA	NA	NA	NA	NA	NA	NF	NF	NF	NA	NA	NA	
BUTYL ACETATE			123-86-4	AF7350000	204-658-1	< 10.0	150	200	150	200	NF	150	200	1700	150 TWA
ETHYL	ACETATE		141-78-6	AH5425000	201-550-6	≤ 10.0	200	400	200	400	NF	NA	NA	2000	400 TWA
				4 . F	IRST AID	MEAS	JRES								
4.1	First Aid:														
	INGESTION:			NG. Contact umber for ass											
				im's head low								lennor	1. II V	Omming	y occors
	EYES:	Splashes are	not likely; h	owever, if pro	duct gets in t	he eyes, f	lush wi	ith cop	ious a	mount	s of luk	ewarn	n wate	er for a	t least 15
		-		e eyelid(s) to e											
	SKIN:			oduct is on the											
				and water. I ing persists, co					g unfil	affer	it has l	been	prope	rly cle	aned. If
	INHALATION:			air at once.					hing st	ops, p	erform	artific	ial res	piratio	n. Seek
		immediate n							•	• • •				•	
4.2	Medical Condition	s Aggravated by E	Exposure:												
	None known.														
					FFIQUEIN	<u> </u>									
				5. FIR	EFIGHTIN	G MEA	V20K	5							
5.1	Flashpoint & Metho														
5.2	80.6 °F (27 °C) Autoignition Tempe														
0.2	NA														
5.3	Flammability Limits			Lower Explo	sive Limit (LEL):	NA		Upper	Explosi	ve Limi	t (UEL)	:	NA	λ
5.4	Fire & Explosion Ha	zards:		•				•				,		•	
	WARNING: Flo	ımmable! Ke	ep away fro	om heat, lit c	igarettes, spo	arks & op	en flar	ne. K	eep c	ontain	er				
	closed. Extinguishing Meth	a da:													
5.5	CO ₂ , Halon, Di		r Foam as a	uthorized										3 入	
5.6	Firefighting Proced	•		5111VII260.								<	1	0	
-	When involved		product will	ignite readily (and decomp	ose to pro	duce	arbon	oxide	s.				\checkmark	
	First responde												/	/	
	equipment. U	-			ect vapors. V	later may	not be	e effec	tive in	actual	ly				
		-	g this produc	t.											
	HAZCHEM CO	DE: 3[Y]E													



Page 3 of 8

Hand	5. Feet. Beauty.								
Pron	ared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards MSDS Revision: 1.4	M	SDS Revision	Date: 09/03/2	2009				
пер		101		Date. 07/03/.	2007				
	6. ACCIDENTAL RELEASE MEASUR	E (
6.1	Spills:	LJ							
0.1	Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate the spill cleanup must wear app	iate Person	al Protective	Fauinment					
	For small spills (e.g., <1 gallon (3.785 liters)) wear appropriate personal protective				Maximize				
	ventilation (open doors and windows) and secure all sources of ignition. Remove spilled material with absorbent material and place into appropriate closed container(s) for disposal. Dispose of properly in accordance with local, state and federal regulations. Wash a affected areas and outside of container with plenty of warm water and soap. Remove any contaminated clothing and wash thoroughly before reuse.								
	For spills ≥ 1 gallon (3.785 liters),, deny entry to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Use ONLY non-sparking tools for recovery and cleanup. Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for proper disposal. Remove contaminated clothing promptly and wash affected skin areas with soap and water. Keep spills and cleaning runoffs out of municipal sewers and open bodies of water.								
	7. HANDLING & STORAGE INFORMA								
7 1	Vork & Hygiene Practices:								
7.1	Avoid prolonged contact with the product. Avoid breathing vapors of this product. exhaust ventilation, fans). Do not eat, drink or smoke while handling product.	Use in a	well-ventilat	ed location (e.g., local				
7.2	Storage & Handling:								
	Keep this material away from heat, sparks and open flame. Open containers slowly on a stable surface. Keep container closed tightly when not in use. Empty container may contain residual amounts of this product; therefore, empty containers should be handled with care.								
	Store containers in a cool, dry location, away from direct sunlight, other light sources incompatible materials (see Section 10).	, or sources	s of intense	heat. Store o	away from				
7.3	Special Precautions:	_							
	Open containers slowly on a stable surface. Keep container tightly closed when not i amounts of this product; therefore, empty containers should be handled with care.	n use. Emp	oty containe	rs may conta	in residual				
	8. EXPOSURE CONTROLS & PERSONAL PRO	OTECTIO	N						
8.1	Ventilation & Engineering Controls:								
	When working with large quantities of product, provide adequate ventilation (e.g., lo eyewash station, sink or washbasin is available in case of exposure to eyes.	ocal exhaus	t ventilation	, fans). Ensu	re that an				
8.2	Respiratory Protection:								
	No special respiratory protection is required under typical circumstances of use or protection authorized per U.S. OSHA's requirement in 29 CFR §1910.134, or applica standards of Canada, its provinces, E.C. member states, or Australia.	-		• •					
8.3	Eye Protection:								
	None required under normal conditions of use. Avoid eye contact. May cause irritation large quantities (e.g., \geq 1 gallon (3.785 liters)), safety glasses with side shields should be		ensitive indi	viduals. Whe	n handling				
8.4	Hand Protection:								
	None required under normal conditions of use. May cause skin irritation in some sensitiv								
0.5	When handling large quantities (e.g., ≥ 1 gallon (3.785 liters)), wear rubber or impervious								
8.5	Body Protection: No apron required when handling small quantities.	HEALTH			1				
	When handling large quantities (e.g., ≥ 1 gallon (3.785 liters)), eye wash stations and		ABILITY		3				
	deluge showers should be available. Upon completion of work activities involving large quantities of this product, wash any exposed areas thoroughly with soap and	REACT	0						
	water.		CTIVE EQ	UIPMENT	Α				
		EYES							



Page 4 of 8

Prep	ared to OSHA, ACC, ANSI, NC	DHSC, WHMIS & 2001/58 EC Standards	MSDS Revision: 1.4	MSDS Revision Date: 09/03/2009							
		9. PHYSICAL & CHEN	NICAL PROPERTIES								
9.1	Density:	1.06 (H₂O = 1)									
9.2	Boiling Point: 212 °F (100 °C) based on Butyl Acetate										
9.3	Melting Point: NA										
9.4	Evaporation Rate:	Evaporation Rate: 0.3 (n-Butyl acetate = 1)									
9.5	Vapor Pressure: NA										
9.6	Molecular Weight:	NA									
9.7	Appearance & Color:	Transparent slightly blue viscous liq	uid with a very mild ester-li	ke odor.							
9.8	Odor Threshold:	ND									
9.9	Solubility:	Insoluble in water.									
9.10	рН	NA									
9.11	Viscosity:	1500-2500 сР									
9.12	Other Information:	VOC: 1.5 lb/gal									
		10. STABILITY &	REACTIVITY								
10.1	Stability:										
		tions when stored properly (see Section	7, Storage and Handling).								
10.2	Hazardous Decomposition Products:	b tomporatures, the products of therm	al decomposition may inc	lude irritating vapors and carbon oxide							
	gases (e.g., CO, CO ₂).	in temperatores, the products of them	iai decomposition may inc	inde initialing vapors and carbon oxide							
10.3	Hazardous Polymerization:										
	Will not occur.										
10.4	Conditions to Avoid:										
	None reported.										
10.5	Incompatible Substances:	with shown widiness (s. s. seconder	ann an aidea) abhan a saide	(a. a. buda ablaria ar muriatia maida) ar							
	strong bases (e.g., lye, potas	•	superoxides), strong acias	(e.g., hydrochloric or muriatic acids), or							
		11. TOXICOLOGICA	L INFORMATION								
11.1	Toxicity Data:										
		n tested on animals to obtain toxicolo In the scientific literature. These data ha		cology data for the components of this is document.							
11.2	Acute Toxicity:										
	See section 2.5										
11.3	Chronic Toxicity: See section 2.6										
11.4	Suspected Carcinogen:										
11.4	No.										
11.5	Reproductive Toxicity:										
		to produce reproductive toxicity in hu	mans.								
	Mutagenicity:	1									
	Embryotoxicity:	to produce mutagenic effects in humo	ins.								
	, ,	to produce embryotoxic effects in hun	nans								
	Teratogenicity:										
	This product is not reported	to produce teratogenic effects in hum	ans.								
_	Reproductive Toxicity:										
11.6	Irritancy of Product:	to produce reproductive effects in hun	nans.								
11.0	See Section 2.3										
11.7	Biological Exposure Indices:										
	NE										
11.8	Physician Recommendations:										
	Treat symptomatically.										



Page 5 of 8

	12. ECOLOGICAL INFORMATION	
2.1	Environmental Stability:	
	The components of this product will slowly degrade over time into a variety of organic compound available for the components of this product are as follows:	s. Specific environmental de
	Butyl Acetate: K _{oc} = 1.82. Water solubility: 120 parts H ₂ O at 77 °F (25 °C). Bioconcentration Factor anticipated to be significant. This compound can be removed from contaminated environ biodegradation. This compound's half-life in water is 6.1 hours.	
	Ethyl Acetate: K _{oc} = 0.73. Water solubility: 64,000 mg/l. Bioconcentration Factor = 4-14. Bioconcentration figuration for the significant. This compound can be removed from contaminated environments from volatilization compound's half-life in water is 6.1 hours.	
.2	Effects on Plants & Animals:	
	There are no specific data available for this product.	
2.3	Effects on Aquatic Life: There are no specific data available for this product; however, very large releases of this product overexposed aquatic life.	ict may be harmful or fatal
	13. DISPOSAL CONSIDERATIONS	
3.1	Waste Disposal: Waste disposal must be in accordance with appropriate Federal, state, and local regulations.	
3.2	Special Considerations:	
	U.S. EPA WASTE NUMBER: D001 (characteristic - ignitable)	
	asic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for	
ddit	ional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG, SCT, ADGR and the CTDGR.	
ddit	49 CFR (GND):	
Addit	49 CFR (GND): CONSUMER COMMODITY, ORM-D (≤ 1.0 L)	
Addit 4.1	49 CFR (GND):	
Addit 4.1	49 CFR (GND): CONSUMER COMMODITY, ORM-D (≤ 1.0 L) UN1263, PAINT, 3, II (> 1.0 L)	
Addit 4.1	49 CFR (GND): CONSUMER COMMODITY, ORM-D (≤ 1.0 L) UN1263, PAINT, 3, II (> 1.0 L) IATA (AIR):	
Addit 4.1	49 CFR (GND): CONSUMER COMMODITY, ORM-D (≤ 1.0 L) UN1263, PAINT, 3, II (> 1.0 L) IATA (AIR): CONSUMER COMMODITY, 9, ID8000 (≤ 0.5 L) PI - 910	
	49 CFR (GND): CONSUMER COMMODITY, ORM-D (≤ 1.0 L) UN1263, PAINT, 3, II (> 1.0 L) IATA (AIR): CONSUMER COMMODITY, 9, ID8000 (≤ 0.5 L) PI - 910 UN1263, PAINT, 3, II, LTD QTY (≤ 1.0 L) PI - Y305 UN1263, PAINT, 3, II (≤ 5.0 L - , ≤1.3212 GALLONS) PI – 305	
Addit 4.1	49 CFR (GND): CONSUMER COMMODITY, ORM-D (≤ 1.0 L) UN1263, PAINT, 3, II (> 1.0 L) IATA (AIR): CONSUMER COMMODITY, 9, ID8000 (≤ 0.5 L) PI - 910 UN1263, PAINT, 3, II, LTD QTY (≤ 1.0 L) PI - Y305	
Addit 4.1 4.2	49 CFR (GND): CONSUMER COMMODITY, ORM-D (≤ 1.0 L) UN1263, PAINT, 3, II (> 1.0 L) IATA (AIR): CONSUMER COMMODITY, 9, ID8000 (≤ 0.5 L) PI - 910 UN1263, PAINT, 3, II, LTD QTY (≤ 1.0 L) PI - Y305 UN1263, PAINT, 3, II (≤ 5.0 L - , ≤1.3212 GALLONS) PI - 305 UN1263, PAINT, 3, II (≤ 60.0 L - , ≤ 15.855 GALLONS) PI - 307	
Addit 4.1 4.2	49 CFR (GND): CONSUMER COMMODITY, ORM-D (≤ 1.0 L) UN1263, PAINT, 3, II (> 1.0 L) IATA (AIR): CONSUMER COMMODITY, 9, ID8000 (≤ 0.5 L) PI - 910 UN1263, PAINT, 3, II, LTD QTY (≤ 1.0 L) PI - Y305 UN1263, PAINT, 3, II (≤ 5.0 L - , ≤1.3212 GALLONS) PI - 305 UN1263, PAINT, 3, II (≤ 60.0 L - , ≤ 15.855 GALLONS) P1 - 307 IMDG (OCN):	
4.1 4.2 4.3	49 CFR (GND): CONSUMER COMMODITY, ORM-D (≤ 1.0 L) UN1263, PAINT, 3, II (> 1.0 L) IATA (AIR): CONSUMER COMMODITY, 9, ID8000 (≤ 0.5 L) PI - 910 UN1263, PAINT, 3, II, LTD QTY (≤ 1.0 L) PI - Y305 UN1263, PAINT, 3, II (≤ 5.0 L - , ≤ 1.3212 GALLONS) PI - 305 UN1263, PAINT, 3, II (≤ 60.0 L - , ≤ 15.855 GALLONS) PI - 307 IMDG (OCN): UN1263, PAINT, 3, II, LTD QTY (≤ 5.0 L) UN1263, PAINT, 3, II, LTD QTY (≤ 5.0 L) UN1263, PAINT, 3, II (> 5.0 L) UN1263, PAINT, 3, II (> 5.0 L) UN1263, PAINT, 3, II (> 5.0 L)	
4.1 4.2 4.3	49 CFR (GND): CONSUMER COMMODITY, ORM-D (≤ 1.0 L) UN1263, PAINT, 3, II (> 1.0 L) IATA (AIR): CONSUMER COMMODITY, 9, ID8000 (≤ 0.5 L) PI - 910 UN1263, PAINT, 3, II, LTD QTY (≤ 1.0 L) PI - Y305 UN1263, PAINT, 3, II (≤ 5.0 L - , ≤1.3212 GALLONS) PI - 305 UN1263, PAINT, 3, II (≤ 60.0 L - , ≤ 15.855 GALLONS) PI - 307 IMDG (OCN): UN1263, PAINT, 3, II, LTD QTY (≤ 5.0 L) UN1263, PAINT, 3, II, LTD QTY (≤ 5.0 L) UN1263, PAINT, 3, II (> 5.0 L) TDGR (Canadian GND): MARK PACKAGE "LIMITED QUANTITY" or "QUANTITÉ LIMITÉE" or "LTD QTY" or "QUANT LTÉE" (≤ 1.0 L)	
4.1 4.2 4.3 4.4	49 CFR (GND): CONSUMER COMMODITY, ORM-D (≤ 1.0 L) UN1263, PAINT, 3, II (> 1.0 L) IATA (AIR): CONSUMER COMMODITY, 9, ID8000 (≤ 0.5 L) PI - 910 UN1263, PAINT, 3, II, LTD QTY (≤ 1.0 L) PI - Y305 UN1263, PAINT, 3, II (≤ 5.0 L - , ≤1.3212 GALLONS) PI - 305 UN1263, PAINT, 3, II (≤ 60.0 L - , ≤ 15.855 GALLONS) PI - 307 IMDG (OCN): UN1263, PAINT, 3, II (≤ 60.0 L - , ≤ 15.855 GALLONS) P1 - 307 IMDG (OCN): UN1263, PAINT, 3, II (> 5.0 L) TDGR (Canadian GND): MARK PACKAGE "LIMITED QUANTITY" or "QUANTITÉ LIMITÉE" or "LTD QTY" or "QUANT LTÉE" (≤ 1.0 L) UN1263, PAINT, 3, II (> 1.0 L)	
Addit 4.1 4.2	49 CFR (GND): CONSUMER COMMODITY, ORM-D (≤ 1.0 L) UN1263, PAINT, 3, II (> 1.0 L) IATA (AIR): CONSUMER COMMODITY, 9, ID8000 (≤ 0.5 L) PI - 910 UN1263, PAINT, 3, II, LTD QTY (≤ 1.0 L) PI - Y305 UN1263, PAINT, 3, II (≤ 5.0 L - , ≤1.3212 GALLONS) PI - 305 UN1263, PAINT, 3, II (≤ 60.0 L - , ≤15.855 GALLONS) PI - 307 IMDG (OCN): UN1263, PAINT, 3, II (≤ 60.0 L - , ≤ 15.855 GALLONS) P1 - 307 IMDG (OCN): UN1263, PAINT, 3, II (> 5.0 L) TDGR (Canadian GND): MARK PACKAGE "LIMITED QUANTITY" or "QUANTITÉ LIMITÉE" or "LTD QTY" or "QUANT LTÉE" (≤ 1.0 L) UN1263, PAINT, 3, II (> 1.0 L) ADR/RID (EU):	
4.1 4.2 4.3 4.4	49 CFR (GND): CONSUMER COMMODITY, ORM-D (≤ 1.0 L) UN1263, PAINT, 3, II (> 1.0 L) IATA (AIR): CONSUMER COMMODITY, 9, ID8000 (≤ 0.5 L) PI - 910 UN1263, PAINT, 3, II, LTD QTY (≤ 1.0 L) PI - Y305 UN1263, PAINT, 3, II (≤ 5.0 L - , ≤1.3212 GALLONS) PI - 305 UN1263, PAINT, 3, II (≤ 60.0 L - , ≤ 15.855 GALLONS) PI - 307 IMDG (OCN): UN1263, PAINT, 3, II (≤ 60.0 L - , ≤ 15.855 GALLONS) P1 - 307 IMDG (OCN): UN1263, PAINT, 3, II (> 5.0 L) TDGR (Canadian GND): MARK PACKAGE "LIMITED QUANTITY" or "QUANTITÉ LIMITÉE" or "LTD QTY" or "QUANT LTÉE" (≤ 1.0 L) UN1263, PAINT, 3, II (> 1.0 L) ADR/RD (EU): UN1263, PAINT, 3, II, 3 °(b). ADR, LTD QTY (≤ 1.0 L)	
Addit 4.1 4.2 4.3 4.4 4.5	49 CFR (GND): CONSUMER COMMODITY, ORM-D (≤ 1.0 L) UN1263, PAINT, 3, II (> 1.0 L) IATA (AIR): CONSUMER COMMODITY, 9, ID8000 (≤ 0.5 L) PI - 910 UN1263, PAINT, 3, II, LTD QTY (≤ 1.0 L) PI - Y305 UN1263, PAINT, 3, II (≤ 5.0 L - , ≤ 1.3212 GALLONS) PI - 305 UN1263, PAINT, 3, II (≤ 60.0 L - , $\leq 1.5.855$ GALLONS) PI - 307 IMDG (OCN): UN1263, PAINT, 3, II, LTD QTY (≤ 5.0 L) UN1263, PAINT, 3, II (> 5.0 L) TDGR (Canadian GND): MARK PACKAGE "LIMITED QUANTITY" or "QUANTITÉ LIMITÉE" or "LTD QTY" or "QUANT LTÉE" (≤ 1.0 L) UN1263, PAINT, 3, II (> 1.0 L) ADR/RID (EU): UN1263, PAINT, 3, II, 3 °(b). ADR, LTD QTY (≤ 1.0 L) UN1263, PAINT 3, 3 10, DR	
4.1 4.2 4.3 4.5	49 CFR (GND): CONSUMER COMMODITY, ORM-D (≤ 1.0 L) UN1263, PAINT, 3, II (> 1.0 L) IATA (AIR): CONSUMER COMMODITY, 9, ID8000 (≤ 0.5 L) PI - 910 UN1263, PAINT, 3, II, LTD QTY (≤ 1.0 L) PI - Y305 UN1263, PAINT, 3, II (≤ 5.0 L - , ≤ 1.3212 GALLONS) PI - 305 UN1263, PAINT, 3, II (≤ 60.0 L - , ≤ 15.855 GALLONS) PI - 307 IMDG (OCN): UN1263, PAINT, 3, II, LTD QTY (≤ 5.0 L) UN1263, PAINT, 3, II, LTD QTY (≤ 5.0 L) UN1263, PAINT, 3, II (> 5.0 L) TDGR (Canadian GND): MARK PACKAGE "LIMITED QUANTITY" or "QUANTITÉ LIMITÉE" or "LTD QTY" or "QUANT LTÉE" (≤ 1.0 L) UN1263, PAINT, 3, II (> 1.0 L) ADR/RID (EU): UN1263, PAINT, 3, II, 3 °(b). ADR, LTD QTY (≤ 1.0 L) UN1263, PAINT, 3, II, 3 °(b). ADR, LTD QTY (≤ 1.0 L) UN1263, PAINT, 3, 3 °(b). ADR	
Addit 4.1 4.2 4.3 4.4	49 CFR (GND): CONSUMER COMMODITY, ORM-D (≤ 1.0 L) UN1263, PAINT, 3, II (> 1.0 L) IATA (AIR): CONSUMER COMMODITY, 9, ID8000 (≤ 0.5 L) PI - 910 UN1263, PAINT, 3, II, LTD QTY (≤ 1.0 L) PI - Y305 UN1263, PAINT, 3, II (≤ 5.0 L - , ≤1.3212 GALLONS) PI - 305 UN1263, PAINT, 3, II (≤ 60.0 L - , ≤ 15.855 GALLONS) PI - 307 IMDG (OCN): UN1263, PAINT, 3, II, LTD QTY (≤ 5.0 L) UN1263, PAINT, 3, II, (≤ 5.0 L) TDGR (Canadian GND): MARK PACKAGE "LIMITED QUANTITY" or "QUANTITÉ LIMITÉE" or "LTD QTY" or "QUANT LTÉE" (≤ 1.0 L) UN1263, PAINT, 3, II (> 5.0 L) ADR/RID (EU): UN1263, PAINT, 3, II, 3 °(b). ADR, LTD QTY (≤ 1.0 L) UN1263, PAINT, 3, II, 3 °(b). ADR, LTD QTY (≤ 1.0 L) UN1263, PAINT, 3, 3 °(b). ADR SCT (MEXICO): UN1263, PINTURA (INFLAMMABLE), 3, II, CANTIDAD LIMITADA (≤ 1.0 L)	
4.3 4.5 4.6	49 CFR (GND): CONSUMER COMMODITY, ORM-D (≤ 1.0 L) UN1263, PAINT, 3, II (> 1.0 L) IATA (AIR): CONSUMER COMMODITY, 9, ID8000 (≤ 0.5 L) PI - 910 UN1263, PAINT, 3, II, LTD QTY (≤ 1.0 L) PI - 9305 UN1263, PAINT, 3, II (≤ 5.0 L - , ≤ 1.3212 GALLONS) PI - 305 UN1263, PAINT, 3, II (≤ 60.0 L - , ≤ 15.855 GALLONS) P1 - 307 IMDG (OCN): UN1263, PAINT, 3, II (≤ 60.0 L - , ≤ 15.855 GALLONS) P1 - 307 IMDG (OCN): UN1263, PAINT, 3, II (> 5.0 L) TDGR (Canadian GND): MARK PACKAGE "LIMITED QUANTIITY" or "QUANTIITÉ LIMITÉE" or "LTD QTY" or "QUANT LTÉE" (≤ 1.0 L) UN1263, PAINT, 3, II (> 1.0 L) ADR/RID (EU): UN1263, PAINT, 3, II, 3 °(b). ADR, LTD QTY (≤ 1.0 L) UN1263, PAINT, 3, II, 3 °(b). ADR, LTD QTY (≤ 1.0 L) UN1263, PAINT, 3, 3 °(b). ADR, LTD QTY (≤ 1.0 L) UN1263, PAINT, 3, 3 °(b). ADR, LTD QTY (≤ 1.0 L) UN1263, PINTURA (INFLAMMABLE), 3, II, CANTIDAD LIMITADA (≤ 1.0 L) UN1263, PINTURA (INFLAMMABLE), 3, II, CANTIDAD LIMITADA (>1.0 L)	
4.1 4.2 4.3 4.4	49 CFR (GND): CONSUMER COMMODITY, ORM-D (≤ 1.0 L) UN1263, PAINT, 3, II (> 1.0 L) IATA (AIR): CONSUMER COMMODITY, 9, ID8000 (≤ 0.5 L) PI - 910 UN1263, PAINT, 3, II, LTD QTY (≤ 1.0 L) PI - Y305 UN1263, PAINT, 3, II (≤ 5.0 L - , ≤1.3212 GALLONS) PI - 305 UN1263, PAINT, 3, II (≤ 60.0 L - , ≤ 15.855 GALLONS) PI - 307 IMDG (OCN): UN1263, PAINT, 3, II, LTD QTY (≤ 5.0 L) UN1263, PAINT, 3, II (> 5.0 L) TDGR (Canadian GND): MARK PACKAGE "LIMITED QUANTITY" or "QUANTITÉ LIMITÉE" or "LTD QTY" or "QUANT LTÉE" (≤ 1.0 L) UN1263, PAINT, 3, II (> 1.0 L) ADR/RID (EU): UN1263, PAINT, 3, II, 3 °(b). ADR, LTD QTY (≤ 1.0 L) UN1263, PAINT, 3, II, 3 °(b). ADR, LTD QTY (≤ 1.0 L) UN1263, PAINT, 3, 3 °(b). ADR SCT (MEXICO): UN1263, PINTURA (INFLAMMABLE), 3, II, CANTIDAD LIMITADA (≤ 1.0 L)	



Page 6 of 8

repa	ared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards MSDS Revision: 1.4 MSDS Revision Date: 09/03/2009							
	15. REGULATORY INFORMATION							
.1	U.S. EPA SARA Title III Reporting Requirements:							
	No chemicals are reportable under Section 313.							
	SARA 304 (40 CFR Table 302.4) - Butyl Acetate, Ethyl Acetate							
	U.S. EPA SARA Title III Threshold Planning Quantity (TPQ):							
	There are no specific Threshold Planning Quantities for the components of this product.							
	U.S. U.S. TSCA Inventory Status:							
	The components of this product are listed on the TSCA Inventory.							
	U.S. CERCLA Reportable Quantity (RQ):							
	Butyl Acetate: 2268 kg; 5000 lbs. Ethyl Acetate: 2268 kg; 5000 lbs.							
	Other U.S. Federal Requirements:							
	This product complies with the appropriate sections of the Food and Drug Administration's 21 CFR subchapter G (Cosmetics).							
b	Other Canadian Regulations:							
	of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. Class B2 Flammable Liquid.							
,	U.S. State Regulatory Information:							
	Butyl Acetate and Ethyl Acetate, are covered under specific state criteria.							
	Components of this product are not listed on the California Proposition 65 lists or they are exempt from the requirements.							
8	European Union 67/548/EEC and Australia NOHSC:2011 (2003) Requirements:							
3	European Union 67/548/EEC and Australia NOHSC:2011 (2003) Requirements: The primary components of this product are not listed in Annex I of EU Directive 67/548/EEC.							
	European Union 67/548/EEC and Australia NOHSC:2011 (2003) Requirements: The primary components of this product are not listed in Annex I of EU Directive 67/548/EEC. <u>Butyl Acetate</u> : Flammable (F). R: Flammable. S: 9-16-33 - Keep container in a well-ventilated place.							
3	European Union 67/548/EEC and Australia NOHSC:2011 (2003) Requirements: The primary components of this product are not listed in Annex I of EU Directive 67/548/EEC.							
	European Union 67/548/EEC and Australia NOHSC:2011 (2003) Requirements: The primary components of this product are not listed in Annex I of EU Directive 67/548/EEC. <u>Butyl Acetate</u> : Flammable (F). R: Flammable. S: 9-16-33 - Keep container in a well-ventilated place. Keep away from sources of ignition - No smoking. Take precautionary measures against static							
}	European Union 67/548/EEC and Australia NOHSC:2011 (2003) Requirements: The primary components of this product are not listed in Annex I of EU Directive 67/548/EEC. <u>Butyl Acetate</u> : Flammable (F). R: Flammable. S: 9-16-33 - Keep container in a well-ventilated place. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. <u>Ethyl Acetate</u> : Flammable, Harmful (F, Xn). R: 11-20-36/37 – Highly flammable. Harmful by inhalation. Irritating to eyes and respiratory system. S: 2-7-16-24/25/26 – Keep out of the reach of children. Keep							
•	European Union 67/548/EEC and Australia NOHSC:2011 (2003) Requirements: The primary components of this product are not listed in Annex I of EU Directive 67/548/EEC. <u>Butyl Acetate</u> : Flammable (F). R: Flammable. S: 9-16-33 - Keep container in a well-ventilated place. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. <u>Ethyl Acetate</u> : Flammable, Harmful (F, Xn). R: 11-20-36/37 – Highly flammable. Harmful by inhalation. Irritating to eyes and respiratory system. S: 2-7-16-24/25/26 – Keep out of the reach of children. Keep container tightly closed. Avoid contact with skin and eyes. In case of contact with eyes, rinse							
\$	European Union 67/548/EEC and Australia NOHSC:2011 (2003) Requirements: The primary components of this product are not listed in Annex I of EU Directive 67/548/EEC. <u>Butyl Acetate</u> : Flammable (F). R: Flammable. S: 9-16-33 - Keep container in a well-ventilated place. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. <u>Ethyl Acetate</u> : Flammable, Harmful (F, Xn). R: 11-20-36/37 – Highly flammable. Harmful by inhalation. Irritating to eyes and respiratory system. S: 2-7-16-24/25/26 – Keep out of the reach of children. Keep container tightly closed. Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Do not empty into drains. Take							
•	European Union 67/548/EEC and Australia NOHSC:2011 (2003) Requirements: The primary components of this product are not listed in Annex I of EU Directive 67/548/EEC. <u>Butyl Acetate</u> : Flammable (F). R: Flammable. S: 9-16-33 - Keep container in a well-ventilated place. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. <u>Ethyl Acetate</u> : Flammable, Harmful (F, Xn). R: 11-20-36/37 – Highly flammable. Harmful by inhalation. Irritating to eyes and respiratory system. S: 2-7-16-24/25/26 – Keep out of the reach of children. Keep container tightly closed. Avoid contact with skin and eyes. In case of contact with eyes, rinse							



Page 7 of 8 CND-N-141

Т

Prep	Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC	Standards	MSDS Revision: 1.4	MSDS Revision Date: 09/03/2009					
	16. OI	HER INFC	ORMATION						
16.1	6.1 Other Information:								
	WARNING FLAMMABLE. Precisely follow directions and	MSDS (availa	ble through your supplie	er) for use. Store in a cool place. Avoid					
	all skin contact. If redness or other signs of adverse reaction occur, discontinue use immediately. Keep tightly sealed. Keep out of								
	sunlight. Keep out of reach of children. For Professiona	I use only.							
16.2	6.2 Terms & Definitions:								
	Please see last page of this MSDS.								
16.3	16.3 Disclaimer:								
	government regulations must be reviewed for applic knowledge, the information contained herein is reliable are not guaranteed and no warranties of any type,	This Material Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's & Creative Nail Design's knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness are not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition							
16.4	 Prepared for: Creative Nail Design, Inc. A Division of Colomer U.S.A., Inc. 1125 Joshua Way Vista, CA 92081 USA (800) 833-NAIL (6245) phone (760) 599-2900 (760) 599-4005 fax http://www.cnd.com/ 								
16.5	 Prepared by: ShipMate, Inc. PO Box 787 Sisters, OR 97759-0787 USA Phone: +1 (310) 370-3600 Fax: +1 (310) 370-5700 e-mail: shipmate@shipmate.com 	Dangerous Goo Training & Cor							



Page 8 of 8

CND-N-141

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards MSDS Revision: 1.4

MSDS Revision Date: 09/03/2009

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a MSDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No.	Chemical Abstract Service Number
---------	----------------------------------

EXPOSURE LIMITS IN AIR:

ACGIH American Conference on Governmental Industrial Hygienist					
TLV Threshold Limit Value					
OSHA	U.S. Occupational Safety and Health Administration				
PEL	Permissible Exposure Limit				
IDLH	Immediately Dangerous to Life and Health				

FIRST AID MEASURES:

CPR	Cardiopulmonary resuscitation - method in which a person whose heart has stopped receives manual chest compressions and breathing to circulate blood and provide oxygen to the body.
-----	---

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: HMIS

HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard		F				
1	Slight Hazard						
2	Moderate Hazard						
3	3 Severe Hazard						
4	Extreme Hazard		Ρ				

HEALTH

PERSONAL PROTECTION RATINGS:

	.KJONAL I	KOIL		1105.							
A	Ś				G	Ś	٩	~~			
в	Ś	<pre></pre>			н	Ĵ	Solution	1	X		
С	Ś	ő	~ *		I	Ś	۹	X			
D		<pre></pre>	~ *		J	(]	٩		R.		
E	Ś	<pre></pre>			к	Ĵ	۹	X	7		
F	F 🖘 💊 📥 🦃				x	X Consult your supervisor or S. for special handling direction					
Sa	Fety Glass	ses	Splash G	Goggles		e Shield a Protectio		Glov	es		
L			ب Synthetia	h.				Dust Res	•		
	Boots		Dust &	io.		ull Face		Airlir	i		
Vap	oor Respire	ator			-	espirator		Hood/M	-		
Vapor Respirator Respirator Respirator Hood/Mask or Note: the dotted circle indicates that this respiratory protective equipment is required for high concentrations or for large volume spills or releases of product. Note:											


FLAMMABILITY LIMITS IN AIR:

Autoignition Temperature	Minimum temperature required to initiate combustion in air with no other source of ignition				
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source				
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source				

NA	Not Available
NR	No Results
NE	Not Established
ND	Not Determined
ML	Maximum Limit
SCBA	Self-Contained Breathing Apparatus

NATIONAL FIRE PROTECTION ASSOCIATION: NFPA HAZARD RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard
ACD	Acidic
ALK	Alkaline
COR	Corrosive
-₩-	Use No Water
ох	Oxidizer



TOXICOLOGICAL INFORMATION:

LD ₅₀	Lethal Dose (solids & liquids) which kills 50% of the exposed animals s						
LC ₅₀	Lethal concentration (gases) which kills 50% of the exposed animal						
ppm	Concentration expressed in parts of material per million parts						
TD _{lo}	Lowest dose to cause a symptom						
TCLo	Lowest concentration to cause a symptom						
TDio, LDio, & LDo Or	Lowest dose (or concentration) to cause lethal or toxic						
TC, TC _o , LC _{io} , & LC _o	effects						
IARC	International Agency for Research on Cancer						
NTP	National Toxicology Program						
RTECS	Registry of Toxic Effects of Chemical Substances						
BCF	Bioconcentration Factor						
TLm	Median threshold limit						
log K _{ow} or log K _{oc}	Coefficient of Oil/Water Distribution						

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System					
DOT	U.S. Department of Transportation					
TC	Transport Canada					
EPA	U.S. Environmental Protection Agency					
DSL	Canadian Domestic Substance List					
NDSL	Canadian Non-Domestic Substance List					
PSL	Canadian Priority Substances List					
TSCA	U.S. Toxic Substance Control Act					
EU	European Union (European Union Directive 67/548/EEC)					
CPR	Canada's Controlled Product Regulations					

EC INFORMATION:

N		1×	*	8	X	×	×
С	E	F	Ν	0	T+	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful

WHMIS INFORMATION:

\oslash	۲	۲		1	۲		R
Α	В	С	D1	D2	D3	E	F
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

OTHER STANDARD ABBREVIATIONS: